

# ARIEL

Vandal proof traditional hand dryer. Wide range of stainless steel finishes available, push button or sensor operating. 360-degree revolving nozzle. Ariel is also available in recessed version or energy saving version .



**ARIEL BF/UV**



**ARIEL LF/UV**



**ARIEL SF/UV**



**ARIEL BP/UV**



**ARIEL LP/UV**



**ARIEL SP/UV**

**Black/anthracite:** on request both push-button and automatic

|                                  |                                 |
|----------------------------------|---------------------------------|
| Cover                            | Stainless steel AISI 304        |
| Wall base                        | Aluminium                       |
| Operating                        | Automatic or Push button        |
| Voltage                          | 220-240 V                       |
| Frequency                        | 50-60 Hz                        |
| Electrical insulation            | Class I                         |
| Protection Level                 | IPX 1                           |
| Motor type                       | Brush                           |
| Brush                            | 1000 hours                      |
| Motor speed                      | 5.500 rpm                       |
| Rated motor power                | 200 W                           |
| Rated heating element power      | 2200 W                          |
| Rated power                      | 2400 W                          |
| Automatic turn-off               | 60 sec. (automatic versions)    |
| Air flow volume                  | 345 mc/h                        |
| Air speed                        | 101 km/h                        |
| Noise level                      | 70 db                           |
| Sensor adjusting                 | YES (automatic versions)        |
| Heating element adjusting        | -                               |
| UV-C lamp                        | 3 W                             |
| Drying time                      | 35 sec.                         |
| Air Temperature                  | 52°                             |
| Antibacterial / antiviral filter | -                               |
| Weight                           | 4,8 Kg                          |
| Measure (H x W x D)              | 243 x 278 x 213 mm              |
| Plug                             | Shuko 16A (cable 85 cm)         |
| Pcs per box                      | Single                          |
| Packaged dimensions (H x W x D)  | 24,5 x 31 x 28 cm               |
| Packaged weight                  | 5,2 Kg (sensor) - 5,6 Kg (push) |
| Packaged volume                  | 0,02 mc                         |
| Pcs per pallet                   | 72 pcs                          |

| Article       | Cover                           | Operating   |
|---------------|---------------------------------|-------------|
| ARIEL BP/UV * | White painted stainless steel   | Push button |
| ARIEL SP/UV * | Satin stainless steel AISI 304  | Push button |
| ARIEL LP/UV * | Bright stainless steel AISI 304 | Push button |
| ARIEL BF/UV   | White painted stainless steel   | Automatic   |
| ARIEL SF/UV   | Satin stainless steel AISI 304  | Automatic   |
| ARIEL LF/UV   | Bright stainless steel AISI 304 | Automatic   |

\* Adjustable timer from 25 to 180 sec.

