



High-speed blade hand dryer: fast drying time, energy efficient, stylish design and very compact in size. Adjustable heating element with auto switch-off probe. Double antibacterial filter as standard equipment. Concealed drip tray traps waste water.



BF



SF

Cover	ABS
Wall base	ABS
Operating	Automatic
Voltage	220-240 V
Frequency	50-60 Hz
Electrical insulation	Classe I
Protection Level	IP 31
Motor type	Brush
Brush	1000 hour
Motor speed	28.000 rpm
Rated motor power	1250 W
Rated heating element power	450 W
Rated power	1700 W
Automatic turn-off	30 sec.
Air flow volume	187 mc/h
Air speed	410 km/h
Noise level	75 db
Water tank capacity	600 ml
Heating element adjusting	YES (ON-OFF)
UV-C lamp	-
Drying time	12 - 15 sec.
Air Temperature	45°
Antibacterial / antiviral filter	2 x EPA E11 (included)
Weight	7,2 Kg.
Measure (H x W x D)	565 x 298 x 170 mm
Plug	Shuko 16A (cable 150 cm)
Pcs per box	Single
Packaged dimensions (H x W x D)	24 x 61 x 35 cm
Packaged weight	8 Kg
Packaged volume	0,05 mc
Pcs per pallet	28

Article	Motor	Cover
XDRY BF	Brush	ABS white
XDRY SF	Brush	ABS grey

