

# Stream Dry UV

**Made in Italy eco-jet hand dryer:** fast drying time, energy efficient, stylish design and very compact in size. Top hygiene level by integrated UV-C lamp **and inbuilt anti-covid filter as standard equipment.** Adjustable heating element. A blue LED light shines on the hands when activated. Wide range of finishes available in plastic as well as in anti-vandal stainless steel.



1100 W



STREAM DRY UV ABS  
STREAM DRY UV BF




STREAM DRY UV LF



STREAM DRY UV SF



STREAM DRY UV NF



Antiviral and antibacterial  
filter included



UV-C LED sanitises the  
insides of the hand dryer

| Article                  | Cover                              |
|--------------------------|------------------------------------|
| <b>STREAM DRY UV ABS</b> | White polypropylene                |
| <b>STREAM DRY UV BF</b>  | White painted stainless steel      |
| <b>STREAM DRY UV LF</b>  | AISI 304 bright stainless steel    |
| <b>STREAM DRY UV SF</b>  | AISI 304 satin stainless steel     |
| <b>STREAM DRY UV NF</b>  | Black matt painted stainless steel |

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Cover                            | Polypropylene - stainless steel      |
| Wall base                        | Nylon                                |
| Operating                        | Automatic                            |
| Voltage                          | 220-240 V                            |
| Frequency                        | 50-60 Hz                             |
| Electrical insulation            | Class II                             |
| Protection Level                 | IP 23                                |
| Motor type                       | Brush                                |
| Brush                            | 1000 hours                           |
| Motor speed                      | 26.000 rpm                           |
| Rated motor power                | 550 W                                |
| Rated heating element power      | 550 W                                |
| Rated power                      | 1100 W                               |
| Automatic turn-off               | 80 - 90 sec.                         |
| Air flow volume                  | 187 mc/h                             |
| Air speed                        | 325 km/h                             |
| Noise level                      | 75 db                                |
| Sensors adjusting                | YES                                  |
| Heating element adjusting        | YES (ON-OFF)                         |
| UV-C lamp                        | 1,5 W                                |
| Drying time                      | 15 sec.                              |
| Air Temperature                  | 45°                                  |
| Antibacterial / antiviral filter | EPA E11 (included)                   |
| Weight                           | 2,55 Kg PP - 3,05 Kg stainless steel |
| Measure (H x W x D)              | 285 x 221 x 157 mm                   |
| Plug                             | Bipolar 10A (cable 120 cm)           |
| Pcs per box                      | Single                               |
| Packaged dimensions (H x W x D)  | 23 x 32 x 23 cm                      |
| Packaged weight                  | 3,2 Kg PP - 3,7 Kg stainless steel   |
| Packaged volume                  | 0,02 mc                              |
| Pcs per pallet                   | 96                                   |

