



High-speed blade hand dryer: superfast, energy efficient, stylish design and ultra compact in size. Top hygiene level by double integrated UV-C lamp **and inbuilt double antiviral / antibacterial filters as standard equipment.** Concealed drip tray traps waste water. Adjustable on/off electrical resistance and probe for detecting the temperature of the airflow.



1450 W



BF



SF



NF

Cover	ABS
Wall base	ABS
Operating	Automatic sensor
Voltage	220-240 Vac
Frequency	50-60 Hz
Electrical insulation	Classe II
Protection Level	IP 31
Motor type	TOP AC
Brush	1000 hours
Motor speed	28.000 rpm
Rated motor power	1100 W
Rated heating element power	350 W
Rated power	1450 W
Automatic turn-off	30 sec.
Air flow volume	187 mc/h
Air speed	410 km/h
Noise level	73 db
Water tank capacity	900 ml
Heating element adjusting	YES (ON-OFF)
UV-C lamp	2 x 1,5 W
Drying time	12 - 15 sec.
Air Temperature	40°
Antibacterial / antiviral filter	2 x EPA E11
Weight	6,56 Kg.
Measure (H x W x D)	566 x 296 x 177 mm
Plug	Schuko 16A (cable 150 cm)
Pcs per box	1
Packaged dimensions (H x W x D)	61 x 35 x 24 cm
Packaged weight	7,7 Kg
Packaged volume	0,05 mc
Pcs per pallet	36

Articolo	Motore	Cover
XDRY COMPACT BF	Brush	ABS white
XDRY COMPACT SF	Brush	ABS grey
XDRY COMPACT NF	Brush	ABS black



Double antibacterial filter



Double UV-C lamp for sanitises the insides of the hand dryer

UV-C LAMP

Led 100.000 hours

ANTIVIRAL and ANTIBACTERIAL FILTER

guarantees protection against 97.66% of virus and bacteria

